

DECLARATION OF PERFORMANCE

According to Annex III

DoP No: FX.951-1-CPR

1. Unique identification code of the product type	FX1 Fix&Go MS Polymer Fast Setting and High Strength Adhesive&Sealant
2. Intended use/es	MS polymer based sealant for facade elements EN 15651-1
3. Manufacturer	Fixa Yapı Kimyasalları San. ve Tic. Ltd. Şti. <i>Finickde Mah. Aziz Cad. No:16 Avcılar/İstanbul /TÜRKİYE</i>
4. Authorised representative	-
5. System/s of AVCP	System 3
6a. Harmonised standard Notified body/ies	EN 15651 Technicky A Skusobny Ustav Stavebny, n.e N.B.: 1301 Studena 3, 82104 Bratislava Slovakia

7. Declared performance/s**Pre-Conditioning: Method A****Substrate: Aluminium****EN 15651-1: F-EXT-INT Class-7,5P**

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to Fire	E	EN 13501 EN 15651
Release of Chemicals Dangerous to the Environment and Health	NPD See SDS	EN 15651
Water Tightness and Air Tightness		EN 15651
Loss of Volume	≤ 25 %	EN ISO 10563 EN 15651
Resistance to Flow	≤ 3 mm	EN ISO 7390 EN 15651
Elongation at Break at 23°C	≥ 25 %	EN ISO 8339 EN 15651
Adhesion/Cohesion at Maintained Extension After Immersion In Water at 23°C	No Failure	EN ISO 10591 EN 15651
Adhesion/Cohesion Properties at Constant Temperatures	No Failure	EN ISO 9046 EN 15651
Durability	Pass	EN 15651
NPD: No Performance Determined		

8. Appropriate technical documentation and/or specific technical documentation

-

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

05.01.2025

Ali EKİN – General Manager

FİXA
YAPI KİMYASALLARI SAN. VE TİC. LTD. ŞTİ.
Firuzköy Mah. Aziz Çelebi No:16 Avcılar İSTANBUL
Tel:(0212) 650 92 82 Fax:(0212) 428 62 85
Avcılar V.D. 330 003 4404 Etiler Beşiktaş/İSTANBUL 806/82172